







TECHNICAL DATASHEET		
Egger Home Laminate Flooring		7/ 31 Classic
Coreboard		HDF swell stopp plus
Profile		The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue. Patented as JUST clic! EP 1 441 087 and EP 1 462 587
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use		31
European Norm EN13329		 EN 13329-31
Format		CLASSIC
Dimension mm (length x width)		1292 x 192
Complete thickness		7
Thickness of silenzio® special cellulose Bevel		-
Pallet		Packaging Euro
Paket information		
	Piece	10
	m ²	2,48
	kg	15,63
Pallet information		
	Piece	520
	m ²	128,99
	kg	826,00
Classification and general requirements according EN13329		
Abrasion resistance according EN13329, annex E		AC3 (IP ≥ 2000)
Impact resistance according EN13329, annex H		Big ball: ≥ 500 mm Small ball: ≥ 8 N
Resistance to staining EN438		Group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425 (Type W)		No change in appearance or damage
Thickness swelling according ISO 24336		≤ 18 %
Tolerance of top layer according EN13329		length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329		grey scale ≥ level 4 (EN:20105-A02)
Static indentation by constant pressure according EN ISO 24343-1		< 0,05
Surface soundness according EN13329, annex D		≥ 1,0 N/mm ²
Thermal resistance according to EN 12667		0,06 m ² K/W

