

TECHNICAL DATASHEET	
Egger Home Laminate Flooring	8/ 31 Classic
Coreboard	E1 HDF swell stopp plus
Profile	The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue. Patented as JUST clic! EP 1 441 087 and EP 1 462 587
Guarantee domestic area	according to Egger Guarantee
Guarantee comercial area	according to Egger Guarantee
Antistatic properties according EN1815	yes, < 2 kV
Class of use	31
European Norm EN13329	EN 13329-31
Format	CLASSIC
Dimension mm (length x width)	1292 x 192
Complete thickness	8
Bevel	-
Profil	JUST clic!
Pallet	Packaging Euro
Paket information	Eulo
Piece	8
m2	1,98
kq	14,54
Pallet information	
Piece	480
m2	119,07
kg	890,00
	Classification and general requirements according EN13329
Abrasion resistance according EN13329, annex E	AC3 (IP ≥ 2000)
Impact resistance according EN13329, annex H	Big ball: ≥ 500 mm Small ball: ≥ 8 N
Resistance to staining EN438	Group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425 (Type W)	No change in appearance or damage
Thickness swelling according ISO 24336	≤ 18 %
Tolerance of top layer according EN13329	length $\pm$ 0,5 mm width $\pm$ 0,1 mm thickness $\pm$ 0,3 mm
Light fastness according EN13329	grey scale ≥ level 4 (EN:20105-A02)
Static indentation by constant pressure according EN ISO 24343-1	< 0,05
Surface soundness according EN13329, annex D	≥ 1,0 N/mm2
Thermal resistance according to EN 12667	0,07 m² K/W













