

TECHNICAL DATASHEET		
EGGER PRO LAMINATE FLOORING		8/32 Aqua Plus
Coreboard		HDF Aqua Plus
Profile		The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use		32
European Norm EN13329		EN 13329-32
Format		CLASSIC
Dimension mm (length x width)		1291 x 193
Complete thickness		8
Thickness of silenizio® special cellulose		
Bevel		WV4
Pallet		Packaging
		One-way-pallet
Paket information		
	Piece	8
	m2	1,99
	kg	14,78
Pallet information		
	Piece	480
	m2	119,60
	kg	910,00
Classification and general requirements according EN13329		
Abrasion resistance according EN13329, annex E		AC4 (IP ≥ 4000)
Impact resistance according EN13329, annex H		Big ball: ≥ 750 mm Small ball: ≥ 12 N
Resistance to staining EN438		Group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425 (Type W)		No change in appearance or damage
Thickness swelling according ISO 24336		≤ 5 % (+/-1)
Tolerance of top layer according EN13329		length ± 0,5 mm width ± 0,1 mm
Light fastness according EN13329		grey scale ≥ level 4 (EN:20105-A02)
Static indentation by constant pressure according EN ISO 24343-1		< 0,05
Surface soundness according EN13329, annex D		≥ 1,0 N/mm2
Thermal resistance according to EN 12667		0,06 m² K/W

