

TECHNICAL DATASHEET

EGGER PRO DESIGN		LARGE	
Coreboard		UWF® - Ultra Wood Fibre	
Profil		The patented UNI fit! installation system stands for a quick and simple installation process. Produced under the licence of Flooring Industries™.	
Guarantee domestic area		according to Egger Guarantee	
Guarantee comercial area		according to Egger Guarantee	
Antistatic properties according EN1815		no	
Class of use	33		
European Norm			
Format	Large	Large	
Dimension mm (length x width)	1295 x 243	1295 x 243	
Complete thickness	5	5	
Integrated underlay	-	-	
Bevel	WW4	WW4+2	
Pallet	Packaging One-way-pallet		
Paket information			
	Piece	8	8
	m ²	2,52	2,52
	kg	11,90	11,90
Pallet information			
	Piece	312	312
	m ²	98,28	98,28
	kg	480,00	480,00
test methode	Classification and general requirements according to EN 16511:2014		
abrasion resistance (testA) according EN 13329, annex E	AC5 (IP ≥ 2000)		
impact resistance according EN13329, annex F	≥ 1600 mm		
Micro scratch resistance according to EN16094	<MSR-A2 <MSR-B2		
Effect of a castor chair according EN425	No change in appearance or damage		
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact		
resistance to staining EN 438 - 2	group 1 + 2: level 5 group 3: level 4		
Thickness swelling according ISO 24336	≤ 5 % (+1%)		
bonding strength [kN/m] according ISO 24334	length side > 1,0 narrow side > 2,0 length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm		
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm		
Dimensional changes due to temperature changes according EN ISO 23999	< 0,25%		
Static indentation by constant pressure according EN ISO 24343-1	≤ 0,2 mm		

disposal key: 170201/630103, municipal law 200138 (vegetal punt) or 200307 (bulky waste)

