







TECHNICAL DATASHEET		
Egger Home Laminate Flooring		8/32 Large WV4
Coreboard		HDF swell stopp plus
Profile		The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use		32
European Norm EN13329		
Format		LARGE
Dimension mm (length x width)		1291 x 246
Complete thickness		8
Thickness of silenzio® special cellulose		
Bevel		WV4 WV2
Pallet		Packaging Euro
Paket information		Euro
	Piece	8
	m2	2,54
	kg	19,04
Pallet information		
	Piece	360
	m2	114,30
	kg	846,00
		Classification and general requirements according EN13329
Abrasion resistance according EN13329, annex E		AC4 (IP ≥ 4000)
Impact resistance according EN13329, annex H		Big ball: ≥ 750 mm Small ball: ≥ 12 N
Resistance to staining EN438		Group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425 (Type W)		No change in appearance or damage
Thickness swelling according ISO 24336		≤ 18 %
Tolerance of top layer according EN13329		length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329		grey scale ≥ level 4 (EN:20105-A02)
Static indentation by constant pressure according EN ISO 24343-1		< 0,05
Surface soundness according EN13329, annex D		≥ 1,25 N/mm2
Thermal resistance according to EN 12667		0,07 m² K/W

