

| TECHNICAL DATASHEET                                              |                                                                   |                                                                                                                                                                |
|------------------------------------------------------------------|-------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Egger Home Laminate Flooring                                     |                                                                   | 8/33                                                                                                                                                           |
| Coreboard                                                        | E1<br>HCHO                                                        | HDF swell stopp plus                                                                                                                                           |
| Profile                                                          | UNI fit<br>Patented                                               | The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™. |
| Guarantee domestic area                                          | 25                                                                | according to Egger Guarantee                                                                                                                                   |
| Guarantee comercial area                                         | 5                                                                 | according to Egger Guarantee                                                                                                                                   |
| Antistatic properties according EN1815                           |                                                                   | yes, < 2 kV                                                                                                                                                    |
| Class of use                                                     | 33                                                                |                                                                                                                                                                |
| European Norm EN13329                                            | EN 13329-33                                                       |                                                                                                                                                                |
| Format                                                           | CLASSIC                                                           |                                                                                                                                                                |
| Dimension mm (length x width)                                    | 1291 x 193                                                        |                                                                                                                                                                |
| Complete thickness                                               | 8                                                                 |                                                                                                                                                                |
| Thickness of silenizio® special cellulose                        |                                                                   |                                                                                                                                                                |
| Bevel                                                            | WV4                                                               |                                                                                                                                                                |
| Profil                                                           |                                                                   |                                                                                                                                                                |
| Packaging                                                        |                                                                   |                                                                                                                                                                |
| Pallet                                                           | Euro                                                              |                                                                                                                                                                |
| Paket information                                                |                                                                   |                                                                                                                                                                |
|                                                                  | Piece                                                             | 8                                                                                                                                                              |
|                                                                  | m2                                                                | 1,99                                                                                                                                                           |
|                                                                  | kg                                                                | 14,54                                                                                                                                                          |
| Pallet information                                               |                                                                   |                                                                                                                                                                |
|                                                                  | Piece                                                             | 480                                                                                                                                                            |
|                                                                  | m2                                                                | 119,60                                                                                                                                                         |
|                                                                  | kg                                                                | 890,00                                                                                                                                                         |
| Classification and general requirements according EN13329        |                                                                   |                                                                                                                                                                |
| Abrasion resistance according EN13329, annex E                   | AC5 (IP ≥ 6000)                                                   |                                                                                                                                                                |
| Impact resistance according EN13329, annex H                     | Big ball: ≥ 1000 mm<br>Small ball: ≥ 15 N                         |                                                                                                                                                                |
| Resistance to staining EN438                                     | Group 1 + 2: level 5<br>group 3: level 5                          |                                                                                                                                                                |
| Effect of furniture leg according EN424                          | No damage shall be visible, when tested with foot Type 0 artefact |                                                                                                                                                                |
| Effect of a castor chair according EN425 (Type W)                | No change in appearance or damage                                 |                                                                                                                                                                |
| Thickness swelling according ISO 24336                           | ≤ 15 %                                                            |                                                                                                                                                                |
| Tolerance of top layer according EN13329                         | length ± 0,5 mm<br>width ± 0,1 mm<br>thickness ± 0,3 mm           |                                                                                                                                                                |
| Light fastness according EN13329                                 | grey scale ≥ level 4 (EN:20105-A02)                               |                                                                                                                                                                |
| Static indentation by constant pressure according EN ISO 24343-1 | < 0,05                                                            |                                                                                                                                                                |
| Surface soundness according EN13329, annex D                     | ≥ 1,25 N/mm2                                                      |                                                                                                                                                                |
| Thermal resistance according to EN 12667                         | 0,07 m² K/W                                                       |                                                                                                                                                                |

