

TECHNICAL DATASHEET		
EGGER BASIC FLOORING		7/ 31 Classic
Coreboard		HDF swell stopp plus
Profile		The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue. Patented as JUST clic! EP 1 441 087 and EP 1 462 587
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		no
Class of use		31
European Norm EN13329		
Format		CLASSIC
Dimension mm (length x width)		1292 x 192
Complete thickness		7
Thickness of silenzio® special cellulose		-
Bevel		-
		Packaging
Pallet		Euro
Paket information		
	Piece	10
	m2	2,48
	kg	15,63
Pallet information		
	Piece	520
	m2	128,99
	kg	838,00
		Classification and general requirements according EN13329
Abrasion resistance according EN13329, annex E		AC3 (IP ≥ 2000)
Impact resistance according EN13329, annex H		Big ball: ≥ 500 mm Small ball: ≥ 8 N
Resistance to staining EN438		Group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425 (Type W)		No change in appearance or damage
Thickness swelling according ISO 24336		≤ 18 %
Tolerance of top layer according EN13329		length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329		grey scale ≥ level 4 (EN:20105-A02)
Static indentation by constant pressure according EN ISO 24343-1		< 0,05
Surface soundness according EN13329, annex D		≥ 1,0 N/mm2
Thermal resistance according to EN 12667		0,06 m² K/W

