

TECHNICAL DATASHEET	
EGGER BASIC FLOORING	
8/ 31 Classic	
Coreboard	HDF swell stopp plus
Profile	The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue. Patented as JUST clic! EP 1 441 087 and EP 1 462 587
Guarantee domestic area	according to Egger Guarantee
Guarantee comercial area	according to Egger Guarantee
Antistatic properties according EN1815	no
Class of use	31
European Norm EN13329	
Format	CLASSIC
Dimension mm (length x width)	1292 x 192
Complete thickness	8
Thickness of silenizio® special cellulose	
Bevel	- / WV4
Pallet	Packaging Euro
Paket information	
Piece	8
m2	1,98
kg	14,46
Pallet information	
Piece	480
m2	119,07
kg	882,00
Classification and general requirements according EN13329	
Abrasion resistance according EN13329, annex E	AC3 (IP ≥ 2000)
Impact resistance according EN13329, annex H	Big ball: ≥ 500 mm Small ball: ≥ 8 N
Resistance to staining EN438	Group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425 (Type W)	No change in appearance or damage
Castor chairs according EN12529	Big ball: ≥ 500 mm Small ball: ≥ 8 N
Thickness swelling according ISO 24336	≤ 18 %
Tolerance of top layer according EN13329	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329	grey scale ≥ level 4 (EN:20105-A02)
Static indentation by constant pressure according EN ISO 24343-1	< 0,05
Surface soundness according EN13329, annex D	≥ 1,0 N/mm2
Thermal resistance according to EN 12667	0,07 m² K/W

