

TECHNICAL DATASHEET		
EGGER PRO DESIGN		LONG
Coreboard		UWF® - Ultra Wood Fibre
Profil		The patented UNI fit! installation system stands for a quick and simple installation process. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		no
Class of use		33
European Norm		EN 16511-33
Format		Long
Dimension mm (length x width)		2050 x 245
Complete thickness		5
Integrated underlay		-
Bevel		WV4
		Packaging
Pallet		One-way-pallet
Paket information		
	Piece	7
	m2	3,51
	kg	16,95
Pallet information		
	Piece	231
	m2	115,83
	kg	579
test methode		Classification and general requirements according to EN 16511:2014
abrasion resistance (testA) according EN 13329, annex E		IP ≥ 2000 Zyklen
impact resistance according EN13329, annex F		≥ 1600 mm
Micro scratch resistance according to EN16094		<MSR-A2 <MSR-B2
Effect of a castor chair according EN425		No change in appearance or damage
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
resistance to staining EN 438 - 2		group 1 + 2: level 5 group 3: level 4
Thickness swelling according ISO 24336		≤ 5 % (+1%)
bonding strength [kN/m] according ISO 24334		length side > 1,0 narrow side > 2,0
tolerance of top layer according ISO 24337		length ± 0,5 mm width ± 0,1 mm thickness ± 0,3 mm
Dimensional changes due to temperature changes according EN ISO 23999		< 0,25%
Static indentation by constant pressure according EN ISO 24343-1		≤ 0,2 mm

disposal key: 170201/030103, municipal law 200138 (varietal purity) or 200307 (bulky waste)

