

**TECHNICAL DATASHEET**

EGGER PRO COMFORT		Classic
Coreboard	E1 HCHO	HDF swell stopp plus
Profil	UNI FIT PROFIT	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	15	according to Egger Guarantee
Guarantee comercial area	5	according to Egger Guarantee
Antistatic properties according EN1815	7	not available
Class of use	31	
European Norm	EN 16511-31	
Format	CLASSIC	
Dimension mm (length x width)	1292 x 195	
Complete thickness	10	
Integrated underlay	yes, made from natural cork	
Bevel	WV4	
Pallet	Packaging One-way-pallet	
Paket information		
	Piece	7
	m2	1,76
	kg	14,22
Pallet information		
	Piece	336
	m2	84,48
	kg	702,00
Classification and general requirements according to EN16511:2014		
abrasion resistance according EN13329, Annex E	AC3 (IP ≥ 600)	
impact resistance according EN13329, Annex F	≥ 800 mm	
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3	
Thickness swelling according ISO 24336	≤ 20 %	
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,3	
Effect of a castor chair according EN425	10.000 Zyklen	
Thermal resistance according to EN 12667	0,09m2 K/W	
Impact Sound Reduction according to EN ISO 10140 -3	≤14 dB	
Room Sound Reduction IHD W 431	50% (1)	

\* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film  
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



Institut Bauen und Umwelt e.V.



PEFC 06-38-171

