

TECHNICAL DATASHEET		
EGGER PRO COMFORT		Kingsize
Coreboard		HDF swell stopp plus
Profil		The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		not available
Class of use		31
European Norm		
Format		Kingsize
Dimension mm (length x width)		1292 x 327
Complete thickness		10
Integrated underlay		yes, made from natural cork
Bevel		WV4
		Packaging
Pallet		One-way-pallet
Paket information		
	Piece	5
	m2	2,11
	kg	17,49
Pallet information		
	Piece	200
	m2	84,4
	kg	720
Classification and general requirements according to EN16511:2014		
abrasion resistance according EN13329, Annex E		IP ≥ 600 cycles
impact resistance according EN13329, Annex F		≥ 800 mm
resistance to staining EN 438 - 2		group 1 + 2: level 4 group 3: level 3
Thickness swelling according ISO 24336		≤ 20 %
tolerance of top layer according ISO 24337		length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Static indentation by constant pressure according EN24343-1 (EN/ISO)		≤ 0,3
Effect of a castor chair according EN425		10.000 Zyklen
Thermal resistance according to EN 12667		0,09m2 K/W
Impact Sound Reduction according to EN ISO 10140 -3		≤14 dB
Room Sound Reduction IHD W 431		50% (1)

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



Institut Bauen und Umwelt e.V.



PEFC/06-38-171

