

TECHNICAL DATASHEET		
EGGER PRO COMFORT		Long
Coreboard	E1 HCHO	HDF swell stopp plus
Profil	UNI FIT UNIFIT	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	15	according to Egger Guarantee
Guarantee comercial area	5	according to Egger Guarantee
Antistatic properties according EN1815	⚡	not available
Class of use		31
European Norm		EN 16511-31
Format		Long
Dimension mm (length x width)		2050 x 245
Complete thickness		10
Integrated underlay		yes, made from natural cork
Bevel		WV4
		Packaging
Pallet		One-way-pallet
Paket information		
	Piece	5
	m2	2,51
	kg	21,19
Pallet information		
	Piece	165
	m2	82,83
	kg	719
Classification and general requirements according to EN16511:2014		
abrasion resistance according EN13329, Annex E		IP ≥ 600 cycles
impact resistance according EN13329, Annex F		≥ 800 mm
resistance to staining EN 438 - 2		group 1 + 2: level 4 group 3: level 3
Thickness swelling according ISO 24336		≤ 20 %
tolerance of top layer according ISO 24337		length ± 0,3 mm width ± 0,1 mm thickness ± 0,5 mm
Static indentation by constant pressure according EN24343-1 (EN/ISO)		≤ 0,3
Effect of a castor chair according EN425		10.000 Zyklen
Thermal resistance according to EN 12667		0,09m2 K/W
Impact Sound Reduction according to EN ISO 10140 - 3		≤14 dB
Room Sound Reduction IHD W 431		50% (1)

\* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film  
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



Institut Bauen und Umwelt e.V.



PEFC®  
PEFC/06-38-171

